

JUICEBOX[®] Pro 32

Commercial Charging Stations

Smarter commercial EV charging made possible with the JuiceBox Pro 32

JuiceBox is a Level 2 charging station with all the charging and safety features businesses and public organizations need to provide smart grid EV charging easily and cost-effectively.

Powered by the JuiceNet[®] smart charging platform, JuiceBox affords both direct user control and smart grid optimization. It offers your customers, employees, and tenants access to best-in-class smart charging solutions and helps you:

- Optimize energy costs by controlling charging times and demand charges
- Conveniently monetize your EV charging
- Increase grid reliability and support EV adoption
- Enhance driver satisfaction and reach sustainability goals



Why JuiceBox?

| | | |
|---|---|--|
| <p>Powered by JuiceNet</p> <p>Intuitive mobile app for drivers and powerful online dashboard for system administrators</p> | <p>Smart Grid Connected</p> <p>Optimize charging times and aggregate stations to reduce energy costs</p> | <p>Great Performance & Value</p> <p>Best-in-class smart charging station at an affordable price</p> |
| <p>Universal Compatibility</p> <p>SAE-J1772[™] compliance ensures compatibility with all EVs*</p> | <p>Access Control & Payment</p> <p>With JuiceNet Enterprise software, allow registered drivers to access charging stations via mobile device and pay to charge with the mobile app</p> | <p>Compact & Easy to Use</p> <p>Small enclosure, weatherproof for indoor/outdoor installation, LED charging status indicators</p> |

*Tesla requires adapter

JuiceBox® Pro 32 Specifications

Electrical Characteristics

- > Safety rated: 32A Max
- > Single phase input: nominal voltage 110-240 VAC ~60 Hz
- > Power: 3.5 kW at 110 VAC; 7.7 kW at 240 VAC

Input Cable & Plug

- > 2 ft/0.6 m with NEMA 14-50 plug
- > 2.5 ft/0.8 m hardwire pigtail

Output Cable & Connector

- > 25 ft/7.6 m cable
- > J1772 standard compliant

JuiceNet® Smart Charging Platform

- > Precision measurement of power, energy, voltage & current
- > Web-based portal: set payment rates and charging hours; monitor charging status and consumption data for individuals or groups of devices; control station access; manage EV load
- > Driver app to monitor and pay for charging (iOS & Android)
- > Refer to the JuiceNet Business and JuiceNet Enterprise data sheets for more on the capabilities of each dashboard

Connectivity & Authentication

- > WiFi-enabled: 802.11 b/g/n 2.4 GHz
- > Integrated Cellular: LTE (optional)
- > JuiceRouter: Connect up to 16 chargers with WiFi-to-LTE router (optional)
- > RFID enabled and QR Code authenticated with JuicePass Enterprise Mobile App

Firmware

- > End-to-end AES-256-based encrypted protocols
- > 90-day, 15-minute interval data storage
- > Over-the-air (OTA) upgradeable firmware
- > Persistent data storage upon power interruption

Enclosure

- > Dynamic LED lights show charging status: network connectivity, charging in progress, delayed charging, standby, charge complete/EV not drawing power
- > IP66: Weatherproof, dust-tight
- > IK10: Resistant polycarbonate case
- > Quick-release wall mounting bracket included
- > Built-in security lock and integrated cable management
- > Operating Temperature: -40°F to 140°F (-40°C to 60°C)

Weight & Dimensions

- > Main enclosure: H: 18.5 in/469 mm x W: 6.8 in/173 mm x D: 5.8 in/147 mm
- > 15 lbs/6.8 kg

Codes & Standards

- > FCC Part 15 Class B, NEC 625 compliant, ENERGY STAR®
- > OCPP 1.6J and OpenADR 2.0b compliant

Safety

- > UL and cUL Listed

Warranty

- > 3-year limited parts warranty for commercial use. 2-year warranty extension available

Made in North America

- > From domestic & imported parts

